

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2019/0294117 A1 Ely et al.

Sep. 26, 2019 (43) **Pub. Date:**

(54) TACTILE SWITCH FOR AN ELECTRONIC DEVICE

(71) Applicant: Apple Inc., Cupertino, CA (US)

Inventors: Colin M. Ely, Sunnyvale, CA (US); John B. Morrell, Los Gatos, CA (US); Duncan Kerr, San Francisco, CA (US); Camille Moussette, Los Gatos, CA (US)

(21) Appl. No.: 16/422,722

(22) Filed: May 24, 2019

Related U.S. Application Data

- (63) Continuation of application No. 16/247,335, filed on Jan. 14, 2019, now Pat. No. 10,331,082, which is a continuation of application No. 16/179,872, filed on Nov. 2, 2018, now Pat. No. 10,331,081, which is a continuation of application No. 16/033,491, filed on Jul. 12, 2018, now Pat. No. 10,216,147, which is a continuation of application No. 15/969,630, filed on May 2, 2018, now Pat. No. 10,175,652, which is a continuation of application No. 15/829,509, filed on Dec. 1, 2017, now Pat. No. 9,971,305, which is a continuation of application No. 15/637,949, filed on Jun. 29, 2017, now Pat. No. 9,836,025, which is a continuation of application No. 15/465,523, filed on Mar. 21, 2017, now Pat. No. 9,709,956, which is a continuation of application No. 15/261,904, filed on Sep. 10, 2016, now Pat. No. 9,620,312, which is a continuation of application No. 14/455,375, filed on Aug. 8, 2014, now Pat. No. 9,627,163.
- (60) Provisional application No. 61/864,389, filed on Aug. 9, 2013.

Publication Classification

(51)	Int. Cl.	
` ′	G04B 27/00	(2006.01)
	G06F 1/16	(2006.01)
	H01H 3/12	(2006.01)
	H01H 9/16	(2006.01)
	G04G 21/08	(2006.01)
	G06F 3/0362	(2006.01)
	G06F 3/0488	(2006.01)
	H01H 25/06	(2006.01)
	H01H 25/00	(2006.01)

(52)U.S. Cl. CPC G04B 27/002 (2013.01); G06F 1/163 (2013.01); H01H 3/122 (2013.01); H01H 9/16 (2013.01); G04G 21/08 (2013.01); G06F 3/0362 (2013.01); H01H 2223/002 (2013.01); H01H 25/06 (2013.01); H01H 25/008 (2013.01); H01H 2209/006 (2013.01); H01H 2215/006 (2013.01); H01H 2221/01 (2013.01);

G06F 3/0488 (2013.01)

(57)ABSTRACT

An electronic watch may include a tactile switch and/or one or more sensors for detecting rotational and translational inputs. The watch may include a display configured to produce graphical outputs that may change in response to rotational inputs, translational inputs, and/or touch inputs received at the display. The watch include a crown positioned along an exterior of the watch enclosure and a shaft coupled to the crown and extending into the enclosure. The tactile switch and/or the one or more sensors may be used to detect rotational and/or translational inputs provided at the crown.

